

Helical **bevel** Gear **Reducers**

FEATURES



The technological content of B-Series gear reducers allows for an **extraordinary performance/lifespan ratio**. These highly versatile gear units are successfully used in a vast number of industrial and civil applications. B-Series units offer **excellent value for money and output torque/weight ratio**, especially considering that they need very limited servicing. The units are available in cast iron (sizes 063 to 163) or aluminium (sizes A42 to A73) casing.



B-PB
Fitted for motor coupling - Coupling with flexible coupling



CB
With compact motor



IB
With input shaft



BA
Fitted for motor coupling



CBA
With compact motor



IBA
With input shaft

CAST IRON

Sizes:

060-080-100-125-140-150-160

- Casing with feet FC, flange SC and universal UC
- Gearing 3 reduction stages
- Gleason spiral bevel gear pairs with run-in profile, mounted as second reduction stage for a higher resistance
- High-strength casings optimized with FEM analysis and input and output flanges of grey cast-iron G200 to ensure top level performances and high reliability
- Excellent mechanical strength
- Gears hardened and tempered with shaved or ground profile
- Load capacity calculated and verified according to ISO 6336 and AGMA 2001
- Painted with RAL 5010 blue epoxy-polyester powder according to DIN 1843
- ATEX versions available 2GD/3GD


ALUMINIUM

Sizes:

A40-A50-A70


- Universal casing
- Gearing with 2 and 3 reduction stages
- Hypoid bevel gears for size A40 and A50, gleason bevel gear pairs for size A70, all with run-in profile
- Casing in die-cast aluminium alloy
- Excellent mechanical strength while being and particularly lightweight
- Gears hardened and tempered with shaved or ground profile
- Load capacity calculated and verified according to ISO 6336 and AGMA 2001
- Painted with RAL 5010 blue epoxy-polyester powder according to DIN 1843
- ATEX version available 3GD

RANGE



	Ø [mm]	Output Torque M ₂ [Nm]	Ratio	
		Max	Min	Max
B063	35 - 40	600	5,71	157,42
B083	40 - 45	850	7,81	144,77
B103	50	1.800	8,13	165,25
B123	60	3.500	7,97	180,40
B143	70	5.000	10,84	187,24
B153	80 - 90	8.000	10,49	165,42
B163	100	13.000	8,89	154,83

- Power from 0,18 up to 90 kW with three phase 4 pole motors
- Reduction ratios between 5,71 and 187,24
- Torque max 13.000 Nm
- Admissible radial loads max 80.000 N



	Ø [mm]	Output Torque M ₂ [Nm]	Ratio	
		Max	Min	Max
BA40	20	120	7,62	78,17
BA50	25 - 28	220	7,91	342,65
BA70	30 - 35	450	8,36	442,76

- Power from 0,12 kW up to 4,8 kW with three phase 4 pole motors
- Reduction ratios between 7,62 and 442,76
- Torque max 450 Nm
- Admissible radial loads max 10.000 N

ACCESSORIES



TorqueArm



Available for the sizes:
063 - 083 - 103 - 123
A40 - A50 - A70



Available for the sizes:
143 - 153 - 163

ShrinkDisk



SolidOutputShaft



Single Output Shaft



Double Output Shaft

OtherAccessories

BackstopDevice
ProtectionCoverkit
ReinforcedOutput

OutputFlange



FA



FB - FC - FD

	FA	FB	FC	FD
B063	•	•	•	/
B083	•	•	•	/
B103	•	•	•	/
B123	•	•	•	/
B143	/	•	/	/
B153	/	•	•	/
B163	/	•	/	/
BA40	•	•	•	•
BA50	•	•	•	•
BA70	•	•	/	/

• Available
/ Not available

VERSIONS



B... SC
Flange Mounting



B... FC
Foot Mounting



B... UC
Foot/Flange Mounting

Different versions are available with hollow output shafts and single/double solid output shafts.



BA.. 2 Stages
Foot/Flange Mounting



BA.. 3 Stages
Foot/Flange Mounting

Different versions are available with hollow output shafts.
Single/double solid output shafts are only available for the BA70.

WORLDWIDE



WEST

1-800-661-4023

TECO   **Westinghouse**
MOTORS (CANADA) INC.
tecowestinghouse.ca

C GR-BS 01-16

EAST

1-800-268-4770